

Vistalon™ 7602

Ethylene Propylene Diene Terpolymer Rubber

Product Description	Key Features
Vistalon 7602 EPDM rubber is a high ENB polymer with low ethylene and medium Mooney. It has broad molecular weight distribution for excellent compounding processibility. It is applicable for extruded applications like weatherseals and glazing seals that need fast cure rate and good compression set. It may also be used in molded applications requiring fast cure rates.	Designed for: <ul style="list-style-type: none"> • Excellent processibility resulting in shorter mixing and molding times. • Good low temperature properties. • Good low temperature flexibility and compression set. • Fast cure rate and high cure state.

General			
Availability ¹	<ul style="list-style-type: none"> • Africa & Middle East • Asia Pacific 	<ul style="list-style-type: none"> • Europe • Latin America 	<ul style="list-style-type: none"> • North America • South America
Revision Date	• 04/27/2012		

Physical	Typical Value (English)	Typical Value (SI)	Test Based On
Mooney	65 MU	65 MU	ASTM D1646
Viscosity ² (ML 1+4, 257°F (125°C))			
Ethylene Content	55.0 wt%	55.0 wt%	ASTM D3900
Ethylidenenorbornene (ENB) Content	7.5 wt%	7.5 wt%	ASTM D6047

Legal Statement

For detailed Product Stewardship information, please contact Customer Service.

This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of ExxonMobil Chemical as to the intended use.

Notes

¹ Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

² Radial cavity dies, polymer remassed at 145±10°C.

For additional technical, sales and order assistance:

Worldwide and the Americas	Asia Pacific	Europe, Middle East and Africa
ExxonMobil Chemical Company 13501 Katy Freeway Houston, TX 77079-1398 USA 1-281-870-6050	ExxonMobil Chemical Asia Pacific 1 HarbourFront Place #06-00 HarbourFront Tower One Singapore 098633 +66-2-1638699	ExxonMobil Chemical Europe Hermeslaan 2 1831 Machelen, Belgium 420-239-016-274

Typical properties: these are not to be construed as specifications.

©2013 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.